

order number: L00872A0003

FO duplex patch cord G50/125 OM3 3,0 m



Fig. may differ

Technical Attributes	
Application	Patch cords
cable diameter mm	2,8 x 5,7
Fiber type	G50/125 OM3
Length	3 m
Housing Colour	aqua
Cable Colour	aqua

Description of the Series/Product Category

Notice: The following information refer to the series/product category as a whole. Please see the specific datasheet for specific technical information of a particular product.

Acc. to ISO/IEC 11801 the fiber channels of duplex connectors are connected, i.e. channel termination A on the 1st side is connected to channel termination B on 2nd side. The channels A/B are marked by differently coloured cable boots (A=red, B=black).

Of all components in a channel, patch cords have to endure highest stress and wear. This is why many users rely on patch cords made by Telegärtner: Perfectly matched components, highest quality standards and completely tracked manufacturing processes make sure the data network works safely and reliably.

Performance Characteristics

- Available for Singlemode and Multimode
- Standard lengths of 1 m, 2 m, 3 m, 5 m and 10 m
- Customer specific lengths available using the TICNET configurator at www.telegaertner.com/ticnet

Mechanical Characteristics	
Cable dimensions in mm: Zipcord	2,8 x 5,7
Cable structure	I-K(ZN)H 2x1 ...
	7 kg/km
Cable dimensions in mm: Minizip	1,8 x 3,7
Max. crush resistance long-term in N/m: Minizip	2000
Cable structure acc. to DIN/VDE 0888	I-K(ZN)H 2x1 ...
Min. bending radius in mm	25
Max. crush resistance long-term in N/m: Zipcord	5000
Colour of outer jacket	aqua
Max. pulling tension short-term/long-term in N: Zipcord	400 / 200
Max. pulling tension short-term/long-term in N: Minizip	240 / 140
	2000 Nm
Bending radius	25
Weight in kg/km: Zipcord	14,5
Weight in kg/km: Minizip	7,4

Climatic Characteristics	
Operating temperature in °C	-5 / +55
Storage temperature in °C	-30 / +70
Installation temperature in °C	-5/ 50
Flame retardancy	IEC 60332-1
Halogen-free acc. to	IEC 60754-2